

The Dissimilarity Representation for Classification

INIT/AERFAI Summer School on MACHINE LEARNING
Benicassim, 25 June 2013

Robert P.W. Duin, Delft University of Technology, <http://rduin.nl/>

(In cooperation with Elzbieta Pekalska)

Pattern Recognition Lab
Delft University of Technology
The Netherlands

<http://37steps.com/disrep-course/>

25 June 2013

The Dissimilarity Representation for Classification

1



Contents

- Intro; Vector Representations
- The Dissimilarity Representation
- Non-Euclidean Representations
- Examples

25 June 2013


The Dissimilarity Representation for Classification

2



Pattern Recognition Problems

Blob Recognition




25 June 2013

The Dissimilarity Representation for Classification

4



Object Recognition




25 June 2013

The Dissimilarity



Pattern Recognition: Speech




25 June 2013

The Dissimilarity Representation for Classification

6



Pattern Recognition: Seismics





Earthquakes

25 June 2013

The Dissimilarity Representation for Classification

7

Pattern Recognition Problems



To which class belongs an **image**

To which class (**segment**) belongs every **pixel**?

Where is an **object** of interest (**detection**); What is it (**classification**)?

25 June 2013

The Dissimilarity Representation for Classification

8

Pattern Recognition: Shape Recognition

Pattern Recognition is very often Shape Recognition:


- Images: B/W, grey value, color, 2D, 3D, 4D
- Time Signals
- Spectra

25 June 2013

The Dissimilarity Representation for Classification

9

Pattern Recognition: Shapes



Examples of objects for different classes



Object of unknown class to be classified

A ? B


25 June 2013

The Dissimilarity Representation for Classification

10

Vector Representation

Pattern Recognition System




25 June 2013

The Dissimilarity Representation for Classification

12

Pattern Recognition System




25 June 2013

The Dissimilarity Representation for Classification

13

Pattern Recognition System




25 June 2013

The Dissimilarity Representation for Classification

14

Pattern Recognition System





25 June 2013

The Dissimilarity Representation for Classification

15

Good Representations

- Class specific
Different classes should be represented in different positions in the representation space.
- Compact
Every class should be represented in a small set of finite domains.



25 June 2013


The Dissimilarity Representation for Classification

16

Compactness

Representations of real world similar objects are close.
There is no ground for any generalization (induction) on representations that do not obey this demand.

(A.G. Arkedev and E.M. Braverman, *Computers and Pattern Recognition*, 1966.)




25 June 2013

The Dissimilarity Representation for Classification

17

True Representations



Similar objects are close
and
Dissimilar objects are distant.

-> no probabilities needed, domains are sufficient!


25 June 2013

The Dissimilarity Representation for Classification

18

Distances and Densities

- ? to be classified as
- B** – because it is most close to an object B
 - A** – because the local density of A is larger.




25 June 2013

The Dissimilarity Representation for Classification

19

Features Reduce



Due to reduction essentially different objects are represented identically.

→ The feature space representation needs a statistical, probabilistic generalization


25 June 2013

The Dissimilarity Representation for Classification

20

Probabilistic Generalization

x = height measured



What is the gender of a person with this height?

Best guess is to choose the most 'probable' class (→ small error).

⇒ Good for overlapping classes.

⇒ Assumes the existence of a probabilistic class distribution and a representative set of examples.

25 June 2013

The Dissimilarity Representation for Classification

21

Bayes decision rule, formal

$$\begin{aligned} p(A|x) &> p(B|x) && \rightarrow A \text{ else } B \\ \text{Bayes: } \frac{p(x|A) p(A)}{p(x)} &> \frac{p(x|B) p(B)}{p(x)} && \rightarrow A \text{ else } B \\ p(x|A) p(A) &> p(x|B) p(B) && \rightarrow A \text{ else } B \end{aligned}$$

$$2\text{-class problems: } S(x) = p(x|A) p(A) - p(x|B) p(B) > 0 \rightarrow A \text{ else } B$$

$$n\text{-class problems: } \text{Class}(x) = \text{argmax}_\omega (p(x|\omega) p(\omega))$$

25 June 2013

The Dissimilarity Representation for Classification

22

Density estimation

- The density is defined on the whole feature space.
- Around object x , the density is defined as:

$$p(x) = \frac{dP(x)}{dx} = \left(\frac{\text{fraction of objects}}{\text{volume}} \right)$$


- Given n measured objects, e.g. person's height (m) how can we estimate $p(x)$?

25 June 2013

The Dissimilarity Representation for Classification

23

The Gaussian distribution (3)



• Normal distribution = Gaussian distribution

• Standard normal distribution:
 $\mu = 0, \sigma^2 = 1$

• 95% of data between $[\mu - 2\sigma, \mu + 2\sigma]$ (in 1D!)


$$p(x) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{1}{2} \frac{(x-\mu)^2}{\sigma^2}\right)$$

25 June 2013

The Dissimilarity Representation for Classification

24

Multivariate Gaussians



$$G = \begin{bmatrix} 3 & 1\frac{1}{2} \\ 1\frac{1}{2} & 2 \end{bmatrix}$$

- k - dimensional density:

$$p(x) = \frac{1}{\sqrt{2\pi^k \det(G)}} \exp\left(-\frac{1}{2}(x-\mu)^T G^{-1}(x-\mu)\right)$$


25 June 2013

The Dissimilarity Representation for Classification


25

Quadratic discriminant functions

$$R(x) = -\frac{1}{2}(x - \hat{\mu}_A)^T \hat{\Sigma}_A^{-1}(x - \hat{\mu}_A) + \frac{1}{2}(x - \hat{\mu}_B)^T \hat{\Sigma}_B^{-1}(x - \hat{\mu}_B) + \text{const}$$




QDC assumes that classes are normally distributed. Wrong decision boundaries are estimated if this does not hold.



25 June 2013


The Dissimilarity Representation for Classification

Linear discriminant function



Normal distributions with equal covariance matrices Σ are optimally separated by a linear classifier

$$R(x) = (\mu_A - \mu_B)^T \Sigma^{-1} x + \text{const}$$



Optimal classifier for normal distributions with unequal covariance matrices Σ_A and Σ_B can be approximated by:

$$R(x) = (\mu_A - \mu_B)^T (p(A)\Sigma_A + p(B)\Sigma_B)^{-1} x + \text{const}$$

25 June 2013

The Dissimilarity Representation for Classification

27

Parzen density estimation (1)


- Fix volume of bin, vary positions of bins, add contribution of each bin
- Define 'bin'-shape (kernel):

$$K(r) > 0$$

$$\int K(r) dr = 1$$

- For test object z sum all bins

$$p(z) = \frac{1}{hn} \sum_i K\left(\frac{z - x_i}{h}\right)$$




25 June 2013

The Dissimilarity Representation for Classification

28

Parzen density estimation (2)

- With Gaussian kernel: $K(x) = \frac{1}{h\sqrt{2\pi}} \exp\left(-\frac{x^2}{2h^2}\right)$




25 June 2013


The Dissimilarity Representation for Classification

29

Parzen: density estimates vs the smoothing parameter



Increasing smoothing parameter h




25 June 2013

The Dissimilarity Representation for Classification

Nearest neighbor rule (1-NN rule)

Assign a new object to the class of the nearest neighbor in the training set.



1-NN rule:

- Often relies on the Euclidean distance. Other distance measures can be used.
- Insensitive to prior probabilities!
- Scaling dependent. Features should be scaled properly.


There are no errors on the training set. The classifier is **overtrained**.

25 June 2013

The Dissimilarity Representation for Classification

31

Support vector machine (SVM)



For linearly-separable classes find the few objects that determine the classifier. These are **support vectors**.

They have the same distance to the classifier: **the margin**.

Identical to "maximum-margin classifier"

$$S(x) = \sum_i \alpha_i (x_i^T x)$$

$$S(x) = w^T x, \min(w^T w)$$

25 June 2013

The Dissimilarity Representation for Classification

32

Pixel Representation

Measuring Human Relevant Information




25 June 2013

The Dissimilarity Representation for Classification

34

Pixel Representation




Pixels are more general, initially complete representation
Large datasets are available → good results for OCR

25 June 2013

The Dissimilarity Representation for Classification

35

Peaking Phenomenon, Overtraining Curse of Dimensionality, Rao's Paradox




25 June 2013

The Dissimilarity Representation for Classification

36

The Connectivity Problem in the Pixel Representation




Dependent (connected) measurements are represented independently. The dependency has to be refound from the data.

25 June 2013

The Dissimilarity Representation for Classification

37

The Connectivity Problem in the Pixel Representation




Reshuffling pixels will not change the classification

25 June 2013

The Dissimilarity Representation for Classification

38

The Connectivity Problem in the Pixel Representation




Interpolation does not yield valid objects

25 June 2013

The Dissimilarity Representation for Classification

39

The Connectivity Problem in the Pixel Representation



Dependent (connected) measurements are represented independently. The dependency has to be refound from the data.

25 June 2013

The Dissimilarity Representation for Classification

40

Reasons for selecting a pixel (sample) representation


- No good features can be found
- Sufficient training samples are available
- Direct, fast classification of the image (linear classifier == convolution)

25 June 2013

The Dissimilarity Representation for Classification

41

Domains instead of Densities



No well sampled training sets are needed.

Statistical classifiers have still to be developed.


Class structure \leftrightarrow Object invariants

25 June 2013

The Dissimilarity Representation for Classification

42

Domain-based Classification



- Do not trust class densities.
- Estimate for each class a domain.
- Outlier sensitive.
- Distances instead of densities


How to construct domain based classifiers?

25 June 2013

The Dissimilarity Representation for Classification

43

Wrong Intuition of High Dimensional Spaces



2D-intuition does not work for high dimensional spaces

All points are boundary points
1000 normally distr. points in R^{20} : 95% on the convex hull.

Points tend to have equal distances
Squared Euclidean distances of points in R^{1024} are distributed as $N(1024, 32\sqrt{2})$, so distances are all equal within 10%.

Class overlap is not visible
1000 points of two 5% overlapping classes in R^{50} can be linearly separable

Moreover:
do real world measurements with $n > 100$ really exist?
⇒ Subspace approaches

25 June 2013

The Dissimilarity Representation for Classification

44

Reasons for selecting a pixel (sample) representation

- No good features can be found
- Sufficient training samples are available
- Direct, fast classification of the image
(linear classifier == convolution)

25 June 2013

The Dissimilarity Representation for Classification

45

Vector Representations

- Features: reduce → class overlap
- Pixels: dimensionality problems
- Dissimilarities?

25 June 2013

The Dissimilarity Representation for Classification

46