

Non-Euclidean Representations

Causes, Corrections, Informativeness

Non-Euclidean Representations: Causes

Computational Noise

Even for Euclidean distance matrices zero eigenvalues may show negative, e.g:

- $X = N(50, 20)$: 50 points in 20 dimensions
- $D = \text{Dist}(X)$: 50 x 50 distance matrix
- Expected: $49 - 20 = 29$ zero eigenvalues
- Found: 15 negative eigenvalues

Lack of information



1800:
Crossing the Jostedalbreen was impossible.
Travelling around (200 km) lasted 5 days.
Until the shared point X was found.
People could visit each other in 8 hours.

$D(V, J) = 5$ days
 $D(V, X) = 4$ hours
 $D(X, J) = 4$ hours


25 June 2013

The Dissimilarity Representation for Classification

88

Computational Problems


Large distances are overestimated
due to computational problems



Weighted edit distance for strings

Projections - Occlusions

Small distances are underestimated



non-metric data due to
partially observed projections

25 June 2013

The Dissimilarity Representation for Classification


90

25 June 2013

The Dissimilarity Representation for Classification

91


Projections - Occlusions



Example: consumer preferences for recommendation systems

Graph Matching → Dissimilarities

Representation by Connected Graphs




Graph (Nodes, Edges, Attributes)
Distance (Graph_1, Graph_2)


Intrinsically Non-Euclidean Dissimilarity Measures
Single Linkage



Distance(Table,Book) = 0
Distance(Table,Cup) = 0
Distance(Book,Cup) = 1




Boundary distances




A set of boundary distances may characterize sets of datapoints:
Distances → features


Intrinsically Non-Euclidean Dissimilarity Measures
Mahalanobis



Intrinsically Non-Euclidean Dissimilarity Measures
Invariants



Intrinsically Non-Euclidean Dissimilarity Measures



Non-Euclidean human relations

25 June 2013

The Dissimilarity Representation for Classification

98

Objects may have an 'inner life'

In dissimilarity measures the 'inner life' of objects may be taken into account (e.g. invariants).

→ Objects cannot be represented anymore as points

→ Non-Euclidean dissimilarities

25 June 2013

The Dissimilarity Representation for Classification

99

Causes of Non-Euclidean Dissimilarities

Computational / Observational Limitations

- numerical accuracy problems
- overestimated large distances (too difficult to compute)
- underestimated small distances (one-sided view of objects)

Essential non-Euclidean distance definitions

- the human distance concept differs from the mathematical one
- no global framework
- invariants

25 June 2013

The Dissimilarity Representation for Classification


100

Euclidean corrections for non-Euclidean dissimilarities

SSSPR 2008

R.P.W. Duin, E. Pekalska, A. Harol, W.J. Lee and H. Bunke

Alternative 2: Embedding



25 June 2013

The Dissimilarity Representation for Classification

102

(Pseudo-)Euclidean Embedding

$m \times m$ D is a given, imperfect dissimilarity matrix of training objects.

Construct inner-product matrix: $B = -\frac{1}{2}JD^{(2)}J$ $J = I - \frac{1}{m}\mathbf{1}\mathbf{1}^T$

Eigenvalue Decomposition, $B = Q\Lambda Q^T$

Select k eigenvectors: $X = Q_k\Lambda_k^{-\frac{1}{2}}$ (problem: $\Lambda_k < 0$)

Let \mathfrak{I}_k be a $k \times k$ diag. matrix, $\mathfrak{I}_k(i,i) = \text{sign}(\Lambda_k(i,i))$

$\Lambda_k(i,i) < 0 \rightarrow$ Pseudo-Euclidean

$n \times m$ D_z is the dissimilarity matrix between new objects and the training set.

The inner-product matrix: $B_z = -\frac{1}{2}(D_z^{(2)}J - \frac{1}{n}\mathbf{1}\mathbf{1}^T D^{(2)}J)$

The embedded objects: $Z = B_z Q_k |\Lambda_k|^{-\frac{1}{2}} \mathfrak{I}_k$

25 June 2013

The Dissimilarity Representation for Classification



103

PES: Pseudo-Euclidean Space (Krein Space)


If D is non-Euclidean, B has p positive and q negative eigenvalues. A pseudo-Euclidean space \mathcal{E} with signature (p, q) , $k = p + q$, is a non-degenerate inner product space $\mathfrak{H}_k = \mathfrak{H}_p \oplus \mathfrak{H}_q$ such that:

$$\langle x, y \rangle_{\mathcal{E}} = x^T \mathfrak{I}_{pq} y = \sum_{i=1}^p x_i y_i - \sum_{j=p+1}^q x_j y_j \quad \mathfrak{I}_{pq} = \begin{bmatrix} I_{p \times p} & 0 \\ 0 & -I_{q \times q} \end{bmatrix}$$

$$d_{\mathcal{E}}^2(x, y) = \langle x - y, x - y \rangle_{\mathcal{E}} = d_p^2(x, y) - d_q^2(x, y)$$



Distances in PES



$$d^2(O, A) > 0$$

$$d^2(O, E) > 0$$

$$d^2(O, B) = 0$$


$$d^2(O, D) < 0$$

All points in the grey area are closer to O than O itself !?

Any point has a negative square distance to some points on the line $v^T J_1 x = 0$.
Can it be used as a classifier?
Can we define a margin as in the SVM?

Pseudo-Euclidean Embedding

If D is non-Euclidean then B has p positive and q negative eigenvalues



Solutions:

- Remove all eigenvectors with small and negative eigenvalues
- or, take absolute values of eigenvalues and proceed
- or, construct a pseudo-Euclidean space

Correction Procedures PES \leftrightarrow ES

- PES:** Pseudo Euclidean Space

$$d_{\mathcal{E}}^2(x, y) = d_p^2(x, y) - d_q^2(x, y)$$

- PES+:** Positive contributions only

$$d_{\mathcal{E}}^2(x, y) = d_p^2(x, y)$$

- AES:** Treat entire space as Euclidean

$$d_{\mathcal{E}}^2(x, y) = d_p^2(x, y) + d_q^2(x, y)$$

Correction Procedures PES \leftrightarrow ES (2)

- DEC:** Enlarging dissimilarities

$$d_{\mathcal{E}}^2(x, y) \leftarrow d_{\mathcal{E}}^2(x, y) + c, x \neq y$$

use smallest c such that $D \succ 0$

- Relax:** Relaxing dissimilarity measure

$$d_{\mathcal{E}}^2(x, y) \leftarrow d_{\mathcal{E}}^2(x, y)^{1/c}, c \geq 1$$

use smallest c such that $D \succ 0$

Correction Procedures PES \leftrightarrow ES (3)

- Laplace:**

Adaptation of Laplace correction from spectral graph theory:

$$d_{\mathcal{E}}^2(x, y) \leftarrow \text{Norm}(d_{\mathcal{E}}^2(x, y))$$

$$d_{\mathcal{E}}^2(x, y) \leftarrow 1 - \delta(x, y) + d_{\mathcal{E}}^2(x, y)$$

$$d_{\mathcal{E}}^2(x, y) \leftarrow d_{\mathcal{E}}^2(x, y) + c, x \neq y \quad D \succ 0$$

- (unpublished result: a 'minimum' Laplace correction can be obtained by normalizing the dissimilarity matrix, followed by the DEC correction)

Example: Chickenpieces (H. Bunke, Bern)



446 binary images, varying size, e.g.: 100 x 130

Andreu, G., Crespo, A., Valiente, J.M.: Selecting the toroidal self-organizing feature maps (TSOFM) best organized to object recogn. In: ICNN. (1997) 1341–1346.

Shape classification by weighted-edit distances (Bunke)


Bunke, H., Buhler, U.: Applications of approximate string matching to 2D shape recognition. Pattern recognition **26** (1993) 1797–1812

25 June 2013

The Dissimilarity Representation for Classification

110

Classification Results for Various Dissimilarity Measures




Best classification result is for a very non-Euclidean dissimilarity measure !

25 June 2013

The Dissimilarity Representation for Classification

111


Eigenspectrum original data (PES)



Classification

112

Eigenspectra corrected data



Representation for Classification

113

Classifiers:

- **1-NN**: 1-Nearest Neighbor (local distances)
- **Parzen**: non-parametric density estimation based on given dissimilarities (local densities)
- **NM**: Nearest Mean Classifier (global distances)
- **QDA**: Quadratic Discriminant Analysis (global densities)


All four classifiers can be computed in ES as well as in PES

25 June 2013



The Dissimilarity Representation for Classification

114

Results







115



Neglecting or sign-changing "negative" directions in the Pseudo-Euclidean Space deteriorates local classifiers (1-NN and Parzen) significantly.

ilarity Representation for Classification

115



ilarity M

Conclusion w.r.t. Euclidean corrections

- Globally sensitive classifiers are hardly affected by corrections.
- 1-NN is insensitive to monotonic corrections, but really suffers from crisp corrections in the PES.
- Parzen is always disturbed by corrections, so they damage the local structure in the data.
- Corrections should be studied in relation with the classifier.

25 June 2013

The Dissimilarity Representation for Classification

118


Non-Euclidean Representations: Informativeness

Negative Euclidean Fraction

$$NEF = \frac{\sum_{\lambda_i < 0} |\lambda_i|}{\sum_{\forall \lambda_i} |\lambda_i|}$$

$$0 \leq NEF \leq 1$$

Artificial Example ,Ball Distances



- Generate sets of balls (classes) uniformly, in a (hyper)cube; not intersecting.
- Balls of the same class have the same size.
- Compute all distances between the ball surfaces.
- > Dissimilarity matrix D

25 June 2013

The Dissimilarity Representation for Classification

120

25 June 2013

The Dissimilarity Representation for Classification

121

Balls3D

Classifier	PE Sp	Ass Sp	Pos Sp	Neg Sp	Cor Sp
1-NN	47.4 (2.0)	47.4 (2.0)	47.4 (2.0)	44.2 (1.5)	47.4 (2.0)
Parzen	45.7 (1.7)	45.5 (1.6)	45.6 (1.7)	35.5 (1.7)	45.7 (1.7)
NM	47.5 (2.0)	47.7 (2.0)	47.6 (1.9)	49.6 (0.2)	48.1 (1.8)
SVM-1	50.7 (2.2)	50.0 (2.7)	50.0 (2.5)	62.1 (1.7)	50.1 (2.0)

Classifier	PE Dis Sp	Ass Dis Sp	Pos Dis Sp	Neg Dis Sp	Cor Dis Sp
1-NN	49.8 (2.2)	49.8 (2.2)	49.8 (2.2)	5.1 (0.8)	49.7 (2.2)
Parzen	47.9 (2.2)	47.9 (2.2)	47.9 (2.2)	4.6 (0.5)	47.9 (2.2)
NM	49.8 (2.2)	49.8 (2.2)	49.8 (2.2)	5.0 (0.8)	49.9 (2.2)
SVM-1	50.2 (1.6)	50.8 (1.7)	50.7 (1.7)	1.9 (0.5)	49.8 (1.5)

10 x (2-fold crossvalidation of 50 objects per class)

25 June 2013

The Dissimilarity Representation for Classification

122



Representation Strategies

Avoiding the PE space

Dissimilarity Space: $X = D$

Correcting

Associated space $X = \{[Xp, Xq], \emptyset\}$ $\tilde{d}_{ij}^2 = d_p^2(x_i, x_j) + d_q^2(x_i, x_j)$

Positive space $X = X_p$ $\tilde{d}_{ij}^2 = d_p^2(x_i, x_j)$

Negative space $X = X_q$ $\tilde{d}_{ij}^2 = d_q^2(x_i, x_j)$

Additive Correction $\tilde{d}_{ij}^2 = d_{ij}^2 + c, i \neq j$ $X = \text{Embedding}(\tilde{D})$

As it is

Pseudo Euclidean Space $X = \{Xp, Xq\}$ $d_{ij}^2 = d_p^2(x_i, x_j) - d_q^2(x_i, x_j)$

Classifiers to be developed further

25 June 2013

The Dissimilarity Representation for Classification

123



	size	classes	Non-Metric	NEF	Rand Err	Original, D	Positive, D_p	Negative, D_q
Chickenpieces45	446	5	0	0.156	0.791	0.022	0.132	0.175
Chickenpieces60	446	5	0	0.162	0.791	0.020	0.067	0.173
Chickenpieces90	446	5	0	0.152	0.791	0.022	0.052	0.148
Chickenpieces120	446	5	0	0.130	0.791	0.034	0.108	0.148
FlowCyto	612	3	1e-5	0.244	0.598	0.103	0.100	0.327
WoodyPlants50	791	14	5e-4	0.229	0.928	0.075	0.076	0.442
CatCortex	65	4	2e-3	0.208	0.738	0.046	0.077	0.662
Protein	213	4	0	0.001	0.718	0.001	0.001	0.001
Balls3D	200	2	3e-4	0.001	0.500	0.470	0.495	0.000
GaussM1	500	2	0	0.262	0.500	0.202	0.202	0.228
GaussM02	500	2	5e-4	0.393	0.500	0.204	0.174	0.252
CoilYork	288	4	8e-8	0.258	0.750	0.267	0.313	0.618
CoilDelftSame	288	4	0	0.027	0.750	0.413	0.417	0.597
CoilDelftDiff	288	4	8e-8	0.128	0.750	0.341	0.341	0.435
NewsGroups	600	4	4e-5	0.202	0.733	0.198	0.213	0.435
BrainMRI	124	2	5e-5	0.112	0.499	0.226	0.218	0.556
Pedestrians	689	3	4e-8	0.111	0.348	0.010	0.015	0.030

Conclusions

- Pseudo Euclidean Space (PES) is sometimes informative (corrections are not helpful).
- The corresponding problems may be intrinsic non-Euclidean
- Classifiers for non-Euclidean data have to be studied further

25 June 2013

The Dissimilarity Representation for Classification

125

